TRADITIONAL OVEN RPM

120

STATIC MONOBLOCK COOKTOP

Small yet with the capacity to bake 5/6 pizzas, either wood or gas fired, this MONOBLOCK auto-dilating baking oven, is ideal for restaurants seating a max of 40/50 people or with anyone who simply wants to provide its clients with an added service without sacrificing too much space.

The cooktop is made in a single refractory block with a thickness of 7 cm and a weight up to 250 kg.

All the Pavesi gas-fired ovens are supplied with an electronically managed gas burner.

Weight Kg. 1100 Dome Thickness cm 8/10 Cook Top - Cover Distance cm 42 Cook top height from ground cm 122 Base Insulation Thickness (Microporous Panels) cm 15 Dome Insulation Thickness (Kaolin Blanket) cm 10 Chimney Flue Ø cm 20 Smokes temperature at the vent 300° - 25 g/sec (50m³/Hr)	Inside Dimentions	cm	120x115
Cook Top - Cover Distance cm 42 Cook top height from ground cm 122 Base Insulation Thickness (Microporous Panels) cm 15 Dome Insulation Thickness (Kaolin Blanket) cm 10 Chimney Flue Ø cm 20	Weight	Kg.	1100
Cook top height from ground cm 122 Base Insulation Thickness (Microporous Panels) cm 15 Dome Insulation Thickness (Kaolin Blanket) cm 10 Chimney Flue Ø cm 20	Dome Thickness	cm	8/10
Base Insulation Thickness (Microporous Panels) cm 15 Dome Insulation Thickness (Kaolin Blanket) cm 10 Chimney Flue Ø cm 20	Cook Top - Cover Distance	cm	42
(Microporous Panels) Dome Insulation Thickness (Kaolin Blanket) Chimney Flue Ø cm 20	Cook top height from ground	cm	122
Blanket) cm 10 Chimney Flue Ø cm 20		cm	15
		cm	10
Smokes temperature at the vent 300° - 25 g/sec (50m³/Hr)	Chimney Flue Ø	cm	20
	Smokes temperature at the vent		300° - 25 g/sec (50m³/Hr)
Static pressure Pa 12	Static pressure	Pa	12
Monoblock Cooking Plate Burner Drago D2	Monoblock Cooking Plate		Burner Drago D2
Thermal Potential Kw min. 6 - max. 34	Thermal Potential	Kw	min. 6 - max. 34
Thermal Potential Kcal/h min. 5.000 - max. 29.200	Thermal Potential	Kcal/h	min. 5.000 - max. 29.200
Gas Pressure Nat. Gas mbar min. 7/20 - max. 25/50	Gas Pressure Nat. Gas	mbar	min. 7/20 - max. 25/50
Gas Flow Nat. Gas Nm³/h min. 0,63/0,20 max. 3,59/1,22	Gas Flow Nat. Gas	Nm³/h	
Gas Coupling inches 1/2	Gas Coupling	inches	1/2
Weight kg. 8	Weight	kg.	8
Electrical Power Supply V 230 Single phase	Electrical Power Supply	V	230 Single phase
Consumption W 100	Consumption	W	100



Because Pavesi oven is hand made and assembled, slight variations in the measures of the final product are normal

















